3/8" X 4" TYPE 316L STAINLESS SADDLE VARIABLE GROUT 1/4" STEEL 6" OF STRAIGHT THREAD FOR ADJUSTMENT .e. .so. - 3" 316 STAINLESS FLANGE BASE W/4-3/4" BOLT HOLES 3" 316L STAINLESS STEEL RETAINING COLLAR 3/8" 316L STAINLESS GUSSETS ON 8" AND LARGER SIZES 3" SCH. 40 316L STAINLESS STEEL RISER STAINLESS STEEL HEIGHT ADJUSTMENT COLLAR W/2" OF STRAIGHT THREAD HEIGHT ADJUSTMENT RISER 2 1/2" SCH. 40 TYPE 316L S.S. 9" LONG 1/2" STAINLESS SET SCREW 6"X14"X14" CONCRETE PIER PICO WATER DISTRICT ₽P ADJUSTABLE PIPE SUPPORT 14" SQ. MITGACIPACA

MININGERAL MANAGER 14" 11 3/4" MIN 16 1/2" MAX S A ALL MATERIALS ARE STANLESS STEEL PER FEDERAL SPECIFICATION AND ASME B31.1 PER 15020-2.1

B PIPE SUPPORT SHALL BE SUPPLIED BY PIPELINE PRODUCTS OR APPROVED EQUAL

C IN EVENT SUPPORT IS MOUNTED ON CONCRETE SLAB OR FLOOR, PIER NOT REQUIRED NOTES: 1/2" PLATE 7-1/2" X 5-1/2":

PROVIDE 1/4" CLEARANCE FROM PIPE.

CONNECT TO FLANGE WITH (2) BOLTS.

LENGTH OF BOLT AS REQ'D. DIAMETER OF

BOLTS SAME AS OTHER BOLTS IN FLANGE REQ'D STD PIPE FLANGE-1/2" STL PLATE 5" MIN THREADING PIPE FLANGE SUPPORT SECTION A-A ⋗ ➤ WELD -2-1/2" STL PIPE √3/8" -STD. FLANGE ATTACHED TO CONC. W/6 SS STUD TYPE WEDGE ANCHORS SIZE 5/8" (4-1/2" MIN. EMBEDMENT) 2-1/2" STEEL PIPE 3"STEEL PIPE COAT AND PAINT SAME AS STEEL PIPING 2-1/2" I.D. THREADED HEX NUT DATE: SEPT 2000 STANDARD DRAWING NUMBER W-32

L

 $\Gamma$